

FK-691-06

Technische Daten | Technical Data

Empf. Mindestrastrabstand <i>rec. centre spacing:</i>	2,54 mm	.100 inches
Federkraft <i>Spring Force:</i>	0,6 N	2.16 oz.
Maximaler Federweg <i>Max. Travel:</i>	1,70 mm	.067 inches
Empfohlener Kontaktthub <i>Recomm. (rated) Travel:</i>	1,00 mm	.039 inches
Temperaturbereich <i>Temperature range:</i>	-55°C bis +250°C	-67°F to +482°F
Typischer Widerstand <i>Typical Resistance:</i>	<15 mΩ	<15 mΩ
Typischer Nennstrom <i>Rated Current Load:</i>	5 A	5 amps
E-Maß <i>Extension Height:</i>	7,40 mm	.291 inches
Bauform, Anschluss <i>Design, Connection Type:</i>	THT-b	

Werkstoffe | Materials

Kolben <i>Plunger:</i>	Bronze, hartvergoldet Bronze, hard gold plated
Gehäusehülse <i>Barrel:</i>	Messing, hartvergoldet Brass, hard gold plated
Feder <i>Spring:</i>	Edelstahl Stainless steel
Kugel <i>Ball:</i>	Edelstahl Stainless steel

