

## FK-691

### Technische Daten | Technical Data

Empf. Mindestrastrabstand   <i>rec. centre spacing:</i>	2,54 mm	.100 inches
Federkraft   <i>Spring Force:</i>	1,0 N	3.60 oz.
Maximaler Federweg   <i>Max. Travel:</i>	1,70 mm	.067 inches
Empfohlener Kontakthub   <i>Recomm. (rated) Travel:</i>	1,00 mm	.039 inches
Temperaturbereich   <i>Temperature range:</i>	-55°C bis +250°C	-67°F to +482°F
Typischer Widerstand   <i>Typical Resistance:</i>	<15 mΩ	<15 mΩ
Typischer Nennstrom   <i>Rated Current Load:</i>	5 A	5 amps
E-Maß   <i>Extension Height:</i>	7,40 mm	.291 inches
Bauform, Anschluss   <i>Design, Connection Type:</i>	THT-b	

### Werkstoffe | Materials

Kolben   <i>Plunger:</i>	Bronze, hartvergoldet   <i>Bronze, hard gold plated</i>
Gehäusehülse   <i>Barrel:</i>	Messing, hartvergoldet   <i>Brass, hard gold plated</i>
Feder   <i>Spring:</i>	Edelstahl   <i>Stainless steel</i>
Kugel   <i>Ball:</i>	Edelstahl   <i>Stainless steel</i>

