

FK-694-S
Technische Daten | Technical Data

Empf. Mindestrastrabstand <i>rec. centre spacing</i> :	2,80 mm	.110 inches
Federkraft <i>Spring Force</i> :	1,0 N	3.59 oz.
Maximaler Federweg <i>Max. Travel</i> :	2,25 mm	.089 inches
Empfohlener Kontakthub <i>Recomm. (rated) Travel</i> :	1,50 mm	.059 inches
Temperaturbereich <i>Temperature range</i> :	-55°C bis +250°C	-67°F to +482°F
Typischer Widerstand <i>Typical Resistance</i> :	50 mΩ	50 mΩ
Typischer Nennstrom <i>Rated Current Load</i> :	3 A	3 amps
E-Maß <i>Extension Height</i> :	11,27 mm	.444 inches
Bauform, Anschluss <i>Design, Connection Type</i> :	SMT	

Werkstoffe | Materials

Kolben <i>Plunger</i> :	Cu-Legierung, vergoldet <i>Copper alloy, gold plated</i>
Gehäusehülse <i>Barrel</i> :	Messing, vergoldet <i>Brass, gold plated</i>
Feder <i>Spring</i> :	Edelstahl <i>Stainless steel</i>
Kugel <i>Ball</i> :	Edelstahl <i>Stainless steel</i>

