

**FK-714**
**Technische Daten | Technical Data**

Empf. Mindestrastrabstand   <i>rec. centre spacing</i> :	2,60 mm	.102 inches
Federkraft   <i>Spring Force</i> :	2,0 N	7.19 oz.
Maximaler Federweg   <i>Max. Travel</i> :	1,70 mm	.067 inches
Empfohlener Kontaktthub   <i>Recomm. (rated) Travel</i> :	1,00 mm	.039 inches
Temperaturbereich   <i>Temperature range</i> :	-55°C bis +250°C	-67°F to +482°F
Typischer Widerstand   <i>Typical Resistance</i> :	15 mΩ	15 mΩ
Typischer Nennstrom   <i>Rated Current Load</i> :	5 A	5 amps
E-Maß   <i>Extension Height</i> :	10,10 mm	.398 inches
Bauform, Anschluss   <i>Design, Connection Type</i> :	THT-b	

**Werkstoffe | Materials**

Kolben   <i>Plunger</i> :	Bronze, vergoldet über Nickel   <i>Bronze, gold plated over nickel</i>
Gehäusehülse   <i>Barrel</i> :	Bronze, vergoldet über Nickel   <i>Bronze, gold plated over nickel</i>
Feder   <i>Spring</i> :	Edelstahl   <i>Stainless steel</i>
Kugel   <i>Ball</i> :	Edelstahl   <i>Stainless steel</i>

