

**FK-715**

**Technische Daten | Technical Data**

Empf. Mindestrastrabstand   <i>rec. centre spacing:</i>	2,90 mm	.114 inches
Federkraft   <i>Spring Force:</i>	0,5 N	1.80 oz.
Maximaler Federweg   <i>Max. Travel:</i>	1,40 mm	.055 inches
Empfohlener Kontakthub   <i>Recomm. (rated) Travel:</i>	0,90 mm	.035 inches
Temperaturbereich   <i>Temperature range:</i>	-55°C bis +250°C	-67°F to +482°F
Typischer Widerstand   <i>Typical Resistance:</i>	20 mΩ	20 mΩ
Typischer Nennstrom   <i>Rated Current Load:</i>	2 A	2 amps
E-Maß   <i>Extension Height:</i>	4,40 mm	.173 inches
Bauform, Anschluss   <i>Design, Connection Type:</i>	THT-b	

**Werkstoffe | Materials**

Kolben   <i>Plunger:</i>	Messing, vergoldet   <b>Brass, gold plated</b>
Gehäusehülse   <i>Barrel:</i>	Messing, vergoldet   <b>Brass, gold plated</b>
Feder   <i>Spring:</i>	Edelstahl   <b>Stainless steel</b>
Kugela   <i>Ball:</i>	Edelstahl   <b>Stainless steel</b>

